



Assembly Instructions for OctopusTap™ Adapter for Bronco Pump™

Congratulations for purchasing the Octopus Adapter designed by a couple of beer fanatics at Brew Innovations LLC. These instructions show our stainless steel 3 Port version but assembly is the same for our 4 Port Plastic version.

Kit Contains:

- Qty 1 303 Stainless Steel or Plastic Octopus Adapter (3 or 4 Port)
- Qty 3 or 4 2' Foot Section of 3/16" Beer Hose
- Qty 3 or 4 Beer Faucets (Attached to above hoses)
- Qty 1 Small Washer
- Qty 1 Large Washer
- Qty 1 Outlet Cover

Instructions:

1. Remove parts from bag and confirm above contents (Fig 1)
2. Remove hose from the existing Bronco Pump, as this is unused and becomes a spare hose (Fig 2)
3. Disassemble your existing Bronco tap by removing the hand-pump from the lower beer shank by twisting the coupler ring in a counter-clockwise direction (Fig 3)
 - If you are unable to do twist this off it can be due to the fact that your Bronco Tap is “fused” together with beer gunk.
 - Soak your entire tap in a bowl of hot water for 30 minutes sucking in water with the entire tap submerged pump and try unscrew again
 - Try soaking the tap over night and try again in the morning
 - If it still will not come apart exchange your Bronco Pump at the liquor store for another one or purchase our fully assembled NEW tap with OctopusTap
4. Clean existing parts (optional)
5. Remove the 2 provided large and small washers from bag and place washers into the grooved out channels on the bottom of the Octopus Adapter. You may have to stretch the larger washer a bit as fits snugly (Fig 4)
6. Screw Firmly Bronco Lower Shank on to Octopus Adapter being sure that washers DO NOT slip out of channels. This will cause leaking if these washers are not aligned correctly. (Fig 5)
7. Screw on Upper Hand-pump on to Octopus Adapter (Fig 6)

8. Heat up a bowl of water in the microwave for 60 seconds or until water is HOT and place the “tips” of the provided hoses in to the water for 60 sec. to soften up the rubber..don't burn yourself
9. Remove hoses from cup of water and firmly push hoses over the 3 barbs on the adapter firmly and let cool for 60 seconds or submerge under cool water. (Fig 7)
10. Place on rubber cap where original hose was removed (Fig 8)
11. Tap the keg and Drink Responsibly (Fig 9)

Fig 1



Fig 2



Fig 3



Fig 4



Fig 5



Fig 6



Fig 7



Fig 8



Fig 9

